

Technical data sheet

Product features



Boiling kettle gas indirect 270 l

Model	SAP Code	00003022
--------------	-----------------	----------



- Device type: Gas unit
- Device heating type: Indirect
- Ignition: Electric
- Steam pressure regulation: Automatic - the pressure switch regulates the performance of the device
- Filling: Semi-automatic
- Jacket filling: Semi-automatic
- Drain: Yes
- Drain valve diameter: 2â€ â€
- Basin dimensions [mm x mm x mm]: 1100 x 550-480
- Basin volume [l]: 270
- Usable volume [l]: 270

SAP Code	00003022	Type of gas	Propane butane, natural gas
Net Width [mm]	1400	Basin volume [l]	270
Net Depth [mm]	900	Usable volume [l]	270
Net Height [mm]	900	Basin dimensions [mm x mm x mm]	1100 x 550-480
Net Weight [kg]	340.00	Device heating type	Indirect
Loading	230 V / 1N - 50 Hz	Steam pressure regulation	Automatic - the pressure switch regulates the performance of the device
Power gas [kW]	44.000		

Technical data sheet

Product benefits



Boiling kettle gas indirect 270 l

Model

SAP Code

00003022

1

Safety element “ thermocouple

safe service for staff
there is no unnecessary gas leakage
long life

- savings on service interventions
- easier and faster operation

2

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

- savings on service interventions
- easy cleaning and maintenance of equipment

3

Smart handle

protection against scalding when lifting the lid
easy handling to operate at any height

- high security
- fewer health problems caused by poor ergonomics

4

Duplicator bottom AISI 316

long service life even in an aggressive salty environment

- savings on service interventions
- avoidance of losses due to interruptions in plant operation

5

All-stainless design including bottom

long service life even in an aggressive salty environment

- savings on service interventions
- easy cleaning and maintenance of equipment

6

Upper hygienic molding with an opening for the drainage of excess contents

spilled or overflowing liquids around the boiler neck can drain into the waste

- easier to keep the workplace clean
- easier to maintain hygiene standards
- easier cleaning of the boiler surface

7

Filling taps for hot and cold water

the possibility of filling the boiler with water from above

- easier filling and draining of water
- easier to wash with hot water
- convenient faucet control on top of the boiler

Technical data sheet

Technical parameters



Boiling kettle gas indirect 270 l

Model

SAP Code

00003022

1. SAP Code:

00003022

2. Net Width [mm]:

1400

3. Net Depth [mm]:

900

4. Net Height [mm]:

900

5. Net Weight [kg]:

340.00

6. Gross Width [mm]:

1400

7. Gross depth [mm]:

900

8. Gross Height [mm]:

950

9. Gross Weight [kg]:

360.00

10. Device type:

Gas unit

11. Construction type of device:

Stationary

12. Loading:

230 V / 1N - 50 Hz

13. Power gas [kW]:

44.000

14. Ignition:

Electric

15. Type of gas:

Propane butane, natural gas

16. Protection of controls:

IPX4

17. Device color:

Stainless steel

18. Material:

AISI 304

19. Indicators:

operation and warm-up

20. Drain valve diameter:

2â€ â€

21. Worktop type:

Molded - comfortable cleaning maintenance

22. Device heating type:

Indirect

23. Basin volume [l]:

270

24. Basin dimensions [mm x mm x mm]:

1100 x 550-480

25. Safety thermocouple:

Yes

26. Adjustable feet:

Yes

27. Bottom material:

AISI 316

28. Usable volume [l]:

270

Technical data sheet

Technical parameters



Boiling kettle gas indirect 270 l

Model

SAP Code

00003022

29. Filling:

Semi-automatic

33. Overflow:

Yes

30. Jacket filling:

Semi-automatic

34. Manometer:

Yes

31. Steam pressure regulation:

Automatic - the pressure switch regulates the performance of the device

35. Water filling type:

Cold

32. Type of drain valve:

conical

36. Drain:

Yes