

Technical data sheet



Product features

Multi-function braising pan electric 6 l TOP 230 V

Model	SAP Code	00010041
--------------	-----------------	----------



- Bottom thickness: 10.00
- Basin volume [l]: 6
- Usable volume [l]: 6
- Protection of controls: IPX4

SAP Code	00010041	Loading	230 V / 1N - 50 Hz
Net Width [mm]	328	Basin volume [l]	6
Net Depth [mm]	630	Usable volume [l]	6
Net Height [mm]	447	Width of internal part [mm]	320
Net Weight [kg]	26.20	Depth of internal part [mm]	530
Power electric [kW]	3.000	Height of internal part [mm]	60

Multi-function braising pan electric 6 l TOP 230 V

Model

SAP Code

00010041

1

All-stainless steel cladding except for the hob

long life
resistance of AISI 304 stainless steel material
the material does not cut

- savings on service interventions
- easier and faster operation

2

Degree of protection of the control elements IPX4

maintenance-free system
resistance to splash water
long life

- savings on service interventions
- greater job security for staff

3

The outlet on the front side is removable

the possibility of draining the oil into the prepared container and a Teflon pin in the container

- easy and safe handling
- better ergonomics and working conditions for operators
- better use of space removability

4

Steel plate

long life
resistance of a ground steel plate with a thickness of 10 mm

- faster warm-up
- toasts better than stainless steel
- food does not stick to it

5

Control on the short side

suitable for lack of space

- possibility of placing more devices

Technical data sheet



Technical parameters

Multi-function braising pan electric 6 l TOP 230 V

Model

SAP Code

00010041

1. SAP Code:

00010041

2. Net Width [mm]:

328

3. Net Depth [mm]:

630

4. Net Height [mm]:

447

5. Net Weight [kg]:

26.20

6. Gross Width [mm]:

375

7. Gross depth [mm]:

685

8. Gross Height [mm]:

450

9. Gross Weight [kg]:

30.50

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

3.000

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Standard equipment for device:

teflon pin with overflow

18. Basin volume [l]:

6

19. Maximum device temperature [°C]:

300

20. Minimum device temperature [°C]:

50

21. Adjustable feet:

Yes

22. Bottom thickness:

10.00

23. Usable volume [l]:

6

24. Type of drain valve:

with safety lock

25. Drain:

Yes

26. Width of internal part [mm]:

320

27. Depth of internal part [mm]:

530

28. Height of internal part [mm]:

60