



Combi convection steam oven STEAMBOX gas 10x GN 1/1 touch screen automatic cleaning direct steam

Model SAP Code 00011597

- Steam type: Injection
- Number of GN / EN: 10
- GN / EN size in device: GN 1/1
- GN device depth: 65
- Control type: Digital
- Humidity control: MeteoSystem regulation based on direct measurement of humidity in the chamber (patented)
- Advanced moisture adjustment: Supersteam two steam saturation modes
- Delta T heat preparation: Yes
- Automatic preheating: Yes
- Multi level cooking: No
- Door constitution: Vented safety double glass, removable for easy cleaning

SAP Code	00011597	Power gas [kW]	19.000
Net Width [mm]	860	Type of gas	Natural Gas
Net Depth [mm]	795	Steam type	Injection
Net Height [mm]	1115	Number of GN / EN	10
Net Weight [kg]	178.00	GN / EN size in device	GN 1/1
Power electric [kW]	0.700	GN device depth	65
Loading	230 V / 1N - 50 Hz	Control type	Digital





Combi convection steam oven STEAMBOX gas 10x GN 1/1 touch screen automatic cleaning direct steam

Model **SAP Code** 00011597

Direct injection

steam generation by spraying water on the heating elements directly in the chamber

- simple and efficient solution
- moist steam with water droplets
- Digital display

simple multi-line backlit display of 99 programs with 9 cooking phases

- help with cooking even for less skilled cooks, safe baking even in the absence of an operator; create your own recipes; easy to use
- Weather system

patented device for measuring steam saturation in real time and in steam mode, the only one on the market

- precise information for the operator about the steam saturation in the cooking area
- Steam tuner

and the kitchen

a control element that enables setting the exact saturation of steam in the cooking chamber during the cooking process

- possibility of cooking different types of cuisine, from very moist steam for typical Czech dishes to lowsaturated steam for e.g. French cuisine
- Pass-through door the door is also built into the back of the combi oven. while full control is retained from the side of the cook enables the distribution of the delivery area
 - the chef can dispense the food through the convecto machine, the customer can see the preparation and maintenance of the food during dispensing
 - **Adaptation for roasting chickens**

the chamber of the convection oven is designed to collect baked fat, the machine is equipped with a container for collecting fat

- grease does not drain into the sewer, does not destroy the machine's waste system

A kit of two machines on top of each other

connection kit allowing two machines to be placed on top of each other

connects the connections, inlets, wastes and ventilation of the lower combi oven

- allows the user to place two machines in smaller spaces to increase production; the chef can prepare two different dishes simultaneously
- **Premix burner**

the only burner with a turbo pre-mixing gas with air on the market

the structure of the burner to V which prevents backfill and banging

This design saves 30 % of gas compared to conventional burners

- faster heat-up faster more comfortable operation
- **Automatic washing**

integrated chamber washing system possibility to use liquid and tablet detergents option to use vinegar as a rinse agent the system simultaneously descales the micro-boiler

- the chamber of the conveyer is washed without the presence of the operator, for example overnight; the system decalcifies the micro-boiler without the need for service intervention; the chamber is maintained in a constant 1% hygienic quality
- **Self-supporting shower**

drum winch integrated in the body of the kettle the shower is inaccessible when the door is closed

- allows food in the food processor to be rinsed out if necessary to speed up cooling
- Six-speed fan, reversible with automatic calculation of direction change

in cooperation with the symbiotic system, it ensures perfect steam distribution without losing its richness its operation is controlled by the program or manually

 allows the preparation of a variety of dishes from the most delicate to high temperature baking at the highest speed

2024-07-05



Technical parameters

Combi convection steam oven STEAMBOX gas 10x GN 1/1 touch screen automatic cleaning direct steam				
Model	SAP Code	00011597		
1. SAP Code: 00011597		14. Type of gas: Natural Gas		
2. Net Width [mm]: 860		15. Material: AISI 304		
3. Net Depth [mm]: 795		16. Exterior color of the device: Stainless steel		
4. Net Height [mm]: 1115		17. Adjustable feet: Yes		
5. Net Weight [kg]: 178.00		18. Humidity control: MeteoSystem - regulation based on direct measurement of humidity in the chamber (patented)		
6. Gross Width [mm]: 955		19. Stacking availability: Yes		
7. Gross depth [mm]: 920		20. Control type: Digital		
8. Gross Height [mm]: 1240		21. Additional information: possibility of reverse door opening - handle on the right side (must be specified when ordering)		
9. Gross Weight [kg]: 188.00		22. Steam type: Injection		
0. Device type: Gas unit		23. Chimney for moisture extraction: Yes		
1. Power electric [kW]: 0.700		24. Delta T heat preparation: Yes		
2. Loading: 230 V / 1N - 50 Hz		25. Automatic preheating: Yes		
3. Power gas [kW]:		26. Automatic cooling:		

Yes

19.000



Technical parameters

Combi convection steam oven STEAMBOX gas 10x GN 1/1 touch screen automatic cleaning direct steam				
Model SAP Code	00011597			
27. Unified finishing of meals EasyService:	40. Shower: volitelná			
28. Night cooking:	41. Distance between the layers [mm]: 70			
29. Washing system: Closed - efficient use of water and washing chemicals by repeated pumping	42. Smoke-dry function: No			
30. Detergent type: Liquid washing detergent + liquid rinse aid/vinegar or washing tablets	43. Interior lighting: Yes			
31. Multi level cooking: No	44. Low temperature heat treatment: Yes			
32. Advanced moisture adjustment: Supersteam - two steam saturation modes	45. Number of fans:			
33. Slow cooking: from 50 °C	46. Number of fan speeds:			
34. Fan stop: Immediate when the door is opened	47. Number of programs: 99			
35. Lighting type: LED lighting in the doors, on both sides	48. USB port: Yes, for uploading recipes and updating firmware			
36. Cavity material and shape: AISI 304, with rounded corners for easy cleaning	49. Door constitution: Vented safety double glass, removable for easy cleaning			
37. Reversible fan: Yes	50. Number of preset programs: 40			
38. Sustaince box: Yes	51. Number of recipe steps: 9			
39. Probe:	52. Minimum device temperature [°C]:			

Optional

50



Technical parameters

Combi convection steam oven STEAMBOX gas 10x GN 1/1 touch screen automatic cleaning direct steam				
Model	SAP Code	00011597		
53. Maximum device temperature [°C]: 300		57. GN / EN size in device: GN 1/1		
54. Device heating type: Combination of steam and hot air		58. GN device depth: 65		
55. HACCP: Yes		59. Food regeneration: Yes		
56. Number of GN / EN:				

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

10