

Technical data sheet



Product features

Steak grill electric 32x48 table durable chrome

Model	SAP Code	00021113
--------------	-----------------	----------



- Griddle dimensions [mm x mm]: 320 x 480 + 320 x 380
- Griddle thickness [mm]: 10.00
- Container for liquid fat: Yes
- Independent heating zones: Separate control for top and bottom plate
- Maximum device temperature [°C]: 300
- Surface finish: durable chrome

SAP Code	00021113	Net Weight [kg]	40.00
Net Width [mm]	705	Power electric [kW]	6.000
Net Depth [mm]	395	Loading	230 V / 1N - 50 Hz
Net Height [mm]	482	Griddle dimensions [mm x mm]	320 x 480 + 320 x 380

Technical data sheet



Product benefits

Steak grill electric 32x48 table durable chrome

Model

SAP Code

00021113

1

Nationheres

Only stainless steel used for food contact

- Absolutely stainless steel and non -magnetic design resists even weaker acids easier to fill hygiene standards (HACCP); Simple maintenance and cleaning

2

Chrome 0.03mm

non -stick dishes when roasting easier to clean the board

- Faster and easier work to operate a higher quality of food

3

Self -controlled control for upper and lower heating

can i control both areas independent of each other

- Better adjustability and saving el. Energy more uniformly cooking I can prepare more types of meals and faster on one device

4

Upper contact area with Teflon canvas

non -backed rollers
uniform warming the rolls

- faster and easier work for service
- faster preparation
- maintaining the shape of food
- faster closed surface of food from both sides of more juicy meat

Technical data sheet



Technical parameters

Steak grill electric 32x48 table durable chrome

Model

SAP Code

00021113

1. SAP Code:

00021113

2. Net Width [mm]:

705

3. Net Depth [mm]:

395

4. Net Height [mm]:

482

5. Net Weight [kg]:

40.00

6. Gross Width [mm]:

395

7. Gross depth [mm]:

705

8. Gross Height [mm]:

482

9. Gross Weight [kg]:

44.00

10. Device type:

Electric unit

11. Construction type of device:

Table top

12. Power electric [kW]:

6.000

13. Loading:

230 V / 1N - 50 Hz

14. Protection of controls:

IPX4

15. Material:

AISI 430

16. Indicators:

operation and warm-up

17. Surface finish:

durable chrome

18. Maximum device temperature [°C]:

300

19. Minimum device temperature [°C]:

50

20. Griddle dimensions [mm x mm]:

320 x 480 + 320 x 380

21. Griddle thickness [mm]:

10.00

22. Container for liquid fat:

Yes

23. Independent heating zones:

Separate control for top and bottom plate

24. Uniform heating:

Yes