

# Technical data sheet

## Product features



### Undercounter dishwasher double skin 40x40 - 230 V

<b>Model</b>	<b>SAP Code</b>	00011272
--------------	-----------------	----------



- Display type: LCD multifunction display
- Number of programs: 9
- Number of skin: 2
- Door clear height [mm]: 320
- Rack size [mm]: 400 x 400
- Water consumption of the washing cycle: 1,2
- Washing cycle time [s]: 90-120-150
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ProGressive + Evolution3 - triple filtration captures particles up to 0.8 mm in size, electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water into the waste

<b>SAP Code</b>	00011272	<b>Boiler power [kW]</b>	2.600
<b>Net Width [mm]</b>	556	<b>Basin volume [l]</b>	8
<b>Net Depth [mm]</b>	466	<b>Tank power [kW]</b>	0.600
<b>Net Height [mm]</b>	695	<b>Water consumption of the washing cycle</b>	1,2
<b>Net Weight [kg]</b>	47.00	<b>Washing cycle time [s]</b>	90-120-150
<b>Power electric [kW]</b>	3.500	<b>Door clear height [mm]</b>	320
<b>Loading</b>	230 V / 1N - 50 Hz	<b>Rack size [mm]</b>	400 x 400
<b>Boiler capacity [l]</b>	2.60		

# Technical data sheet

Technical drawing





Undercounter dishwasher double skin 40x40 - 230 V

Model

SAP Code

00011272



# Technical data sheet

## Product benefits



### Undercounter dishwasher double skin 40x40 - 230 V

Model

SAP Code

00011272

1

#### Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2

#### Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning
- increased user comfort

3

#### LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4

#### Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5

#### Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6

#### Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7

#### Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8

#### Fast heating

Performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

9

#### Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10

#### Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11

#### Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

12

#### Fast heating

performance management allows the current running of the boiler and basins body

- quick fault finding
- transfer of original recipes
- keeping software up to date

# Technical data sheet

Technical parameters



## Undercounter dishwasher double skin 40x40 - 230 V

**Model**

**SAP Code**

00011272

**1. SAP Code:**

00011272

**2. Net Width [mm]:**

556

**3. Net Depth [mm]:**

466

**4. Net Height [mm]:**

695

**5. Net Weight [kg]:**

47.00

**6. Gross Width [mm]:**

516

**7. Gross depth [mm]:**

606

**8. Gross Height [mm]:**

745

**9. Gross Weight [kg]:**

50.00

**10. Device type:**

Electric unit

**11. Control type:**

Digital

**12. Material:**

Stainless steel

**13. Power electric [kW]:**

3.500

**14. Loading:**

230 V / 1N - 50 Hz

**15. Number of programs:**

9

**16. Opening of device:**

Tilting down

**17. Door clear height [mm]:**

320

**18. Adjustable feet:**

Yes

**19. Number of skin:**

2

**20. Self-cleaning cycle:**

Yes

**21. Boiler capacity [ l ]:**

2.60

**22. Boiler power [kW]:**

2.600

**23. Basin volume [l]:**

8

**24. Tank power [kW]:**

0.600

**25. Number of arms for both rinsing and washing:**

2

**26. Arm connection:**

Hand loosen/tighten screw

**27. Washing arm type:**

Rotatable two-pronged

**28. Washing arm material:**

Stainless steel

# Technical data sheet

## Technical parameters



### Undercounter dishwasher double skin 40x40 - 230 V

Model

SAP Code

00011272

#### 29. Atmospheric boiler with rinse pump:

Yes

#### 30. Rinsing arm type:

Rotating two-pronged

#### 31. Rinsing arm material:

Stainless steel

#### 32. Deep drawn tank:

Yes

#### 33. Rack support:

Pressed

#### 34. Tank surface strainers:

stainless steel

#### 35. Drain filter:

ProGressive + Evolution3 - triple filtration captures particles up to 0.8 mm in size, electronically controlled partial discharge before the rinsing phase ensures 0% loss of clean water into the waste

#### 36. Thermostop:

Yes

#### 37. Boiler thermostat adjust:

Yes

#### 38. Rack feed capacity:

24-30-40

#### 39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

#### 40. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

#### 41. Rinse system:

ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure

#### 42. Heating system:

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

#### 43. Quick heating system:

QuickReady - System for rapid heating of water in the tank

#### 44. Hot water electric valve:

Yes

#### 45. Closing door system:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

#### 46. Rack size [mm]:

400 x 400

#### 47. Display type:

LCD multifunction display

#### 48. USB port:

Yes, for Firmware actualisation

#### 49. Drain pump:

Yes

#### 50. Self-diagnostics:

Yes

# Technical data sheet

Technical parameters



## Undercounter dishwasher double skin 40x40 - 230 V

Model

SAP Code

00011272

### 51. Wash pump type:

two-way - DuoFlow

### 52. Detergent dispenser:

Yes

### 53. Rinse aid dispenser:

Yes

### 54. Water consumption of the washing cycle:

1,2

### 55. Washing cycle time [s]:

90-120-150

### 56. Rinse water temperature [°C]:

85

### 57. Standard equipment for device:

2x glass basket, 1x cutlery basket

### 58. Additional information:

The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free

### 59. Program ProSpeed:

Yes

### 60. Program ProFessional:

Yes

### 61. Program ProTemp:

Yes

### 62. Program ProClean:

Yes

### 63. Program ProDrain:

Yes

### 64. Program ProNew:

Yes

### 65. Program ProPlates:

Yes

### 66. Program ProCold:

Yes

### 67. Program ProWater:

Yes