



#### Undercounter dishwasher double skin 50x50 - 400 V

**Model SAP Code** 00011270



- Display type: ProScreen 4 digit display + 2 LED bars
- Number of programs: 7
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle: 1,8
- Washing cycle time [s]: 60-90-180
- Detergent and rinse pump system: ProDose accurate dosing with a peristaltic pump
- Wash pump type: two-way DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011270	Boiler power [kW]	6.000
Net Width [mm]	600	Basin volume [l]	15
Net Depth [mm]	600	Tank power [kW]	1.400
Net Height [mm]	820	Water consumption of the washing cycle	1,8
Net Weight [kg]	54.00	Washing cycle time [s]	60-90-180
Power electric [kW]	7.900	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [ l ]	6.00		





Technical drawing

Undercounter dishwasher double skin 50x50 - 400 V

Model SAP Code 00011270











#### Undercounter dishwasher double skin 50x50 - 400 V

Model SAP Code 00011270

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life
- Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning; higher user comfort
- LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault
- Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump
- Molded basket supports

  guide rails for the baskets molded fro

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life
- Detergent dispenserstwo detergent and rinse aid dispensers
  - precise chemical dosing by ProDose precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel
- **Double filter system**the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency
  - higher washing efficiency; longer life of the washing bath

Fast heating

Performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation
- Protection of fragile dishes
  softstart system for gradual start of washing programs to
  protect fragile dishes
  - protects stemmed glasses and other fragile utensils
- Double shell construction
  - stainless steel construction with insulated double jacket
    - quiet operation
    - energy saving
- Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving
- Fast heating
  performance management allows the current running of the boiler and basins body
  - quick fault finding
  - transfer of original recipes
  - keeping software up to date

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

2024-04-11

3



#### Technical parameters


Undercounter dishwasher double skin 50x50 - 400 V				
Model	SAP Code	00011270		
<b>1. SAP Code:</b> 00011270		15. Number of programs:		
2. Net Width [mm]: 600		<b>16. Opening of device:</b> Tilting down		
<b>3. Net Depth [mm]:</b> 600		17. Door clear height [mm]: 465		
4. Net Height [mm]: 820		18. Inlet pressure: 2-4bar		
<b>5. Net Weight [kg]:</b> 54.00		19. Adjustable feet: Yes		
<b>6. Gross Width [mm]:</b> 650		20. Number of skin:		
7. Gross depth [mm]: 650		21. Self-cleaning cycle: Yes		
8. Gross Height [mm]: 820		22. Boiler capacity [ l ]: 6.00		
<b>9. Gross Weight [kg]:</b> 62.00		<b>23. Boiler power [kW]:</b> 6.000		
10. Device type: Electric unit		24. Basin volume [l]:  15		
11. Control type:  Digital		<b>25. Tank power [kW]:</b> 1.400		
12. Material: Stainless steel		26. Number of arms for both rinsing and washing:		
13. Power electric [kW]: 7.900		27. Arm connection: Click-clack - easy removal with one hand		

28. Washing arm type:

Rotatable two-pronged

14. Loading:

400 V / 3N - 50 Hz





Undercounter dishwasher double skin 50x50 - 400 V		
Model SAP Code	00011270	
29. Washing arm material:  Composite	<b>41. Closing door system:</b> ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes	
30. Rinsing arm type: Rotating two-pronged	<b>42. Rack size [mm]:</b> 500 × 500	
31. Rinsing arm material:  Composite	<b>43. Display type:</b> ProScreen - 4 digit display + 2 LED bars	
32. Deep drawn tank: Yes	<b>44. USB port:</b> Yes, for Firmware actualisation	
33. Rack support:  Pressed	<b>45. Self-diagnostics:</b> Yes	
34. Tank surface strainers: composite	<b>46. Wash pump type:</b> two-way - DuoFlow	
<b>35. Drain filter:</b> ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste	<b>47. Detergent dispenser:</b> Yes	
36. Rack feed capacity: 60-40-20	<b>48. Rinse aid dispenser:</b> Yes	
<b>37. Detergent and rinse pump system:</b> ProDose - accurate dosing with a peristaltic pump	<b>49. Water consumption of the washing cycle:</b> 1,8	
<b>38. Energy Saving system:</b> EnergySaving - Energy saving system due to lowering the boiler temperature	<b>50. Washing cycle time [s]:</b> 60-90-180	
<b>39. Heating system:</b> HotWash - System of simultaneous operation of the heating	51. Rinse water temperature [°C]: 80	

Yes

starting the next cycle

40. Hot water electric valve:

element of the bath and the boiler, reducing the time for

52. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket



#### Technical parameters

Undercounter dishwasher double skin 50x50 - 400 V					
Model	SAP Code	00011270			
<b>53. Additional information:</b> The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free		<b>57. Program ProSelf:</b> Yes			
54. Program ProSpeed:		58. Program ProEco:			
Yes		Yes			
<b>55. Program ProFessional:</b> Yes		59. Program ProLong: Yes			
56. Program ProTemp:		60. Program ProGlass:			

Yes

tel.: +420 381 582 284 e-mail: rmgastro@rmgastro.com web: www.rmgastro.com

Yes