

Technical data sheet

Product features



Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011289
--------------	-----------------	----------



- Display type: ProScreen - 4 digit display + 2 LED bars
- Number of programs: 8
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle: 2,7
- Washing cycle time [s]: 60-90-180
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

SAP Code	00011289	Boiler power [kW]	7.000
Net Width [mm]	633	Basin volume [l]	22
Net Depth [mm]	735	Tank power [kW]	2.500
Net Height [mm]	1562	Water consumption of the washing cycle	2,7
Net Weight [kg]	111.00	Washing cycle time [s]	60-90-180
Power electric [kW]	10.200	Door clear height [mm]	465
Loading	400 V / 3N - 50 Hz	Rack size [mm]	500 x 500
Boiler capacity [l]	6.00		

Technical data sheet

Technical drawing




Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model

SAP Code

00011289



Technical data sheet

Product benefits



Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model

SAP Code

00011289

1

Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2

Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning; higher user comfort

3

LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4

Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5

Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6

Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7

Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8

Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

9

Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10

Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11

Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

Technical data sheet

Technical parameters



Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model	SAP Code	00011289
--------------	-----------------	----------

1. SAP Code:

00011289

15. Number of programs:

8

2. Net Width [mm]:

633

16. Opening of device:

Flip up

3. Net Depth [mm]:

735

17. Door clear height [mm]:

465

4. Net Height [mm]:

1562

18. Inlet pressure:

2-4 bar

5. Net Weight [kg]:

111.00

19. Adjustable feet:

Yes

6. Gross Width [mm]:

870

20. Number of skin:

2

7. Gross depth [mm]:

760

21. Self-cleaning cycle:

Yes

8. Gross Height [mm]:

1540

22. Boiler capacity [l]:

6.00

9. Gross Weight [kg]:

121.00

23. Boiler power [kW]:

7.000

10. Device type:

Electric unit

24. Basin volume [l]:

22

11. Control type:

Digital

25. Tank power [kW]:

2.500

12. Material:

Stainless steel

26. Number of arms for both rinsing and washing:

2

13. Power electric [kW]:

10.200

27. Arm connection:

Click-clack - easy removal with one hand

14. Loading:

400 V / 3N - 50 Hz

28. Washing arm type:

Rotatable two-pronged

Technical data sheet

Technical parameters



Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model

SAP Code

00011289

29. Washing arm material:

Composite

30. Rinsing arm type:

Rotating two-pronged

31. Rinsing arm material:

Composite

32. Deep drawn tank:

Yes

33. Rack support:

Pressed

34. Tank surface strainers:

composite

35. Drain filter:

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

36. Thermostop:

Yes

37. Boiler thermostat adjust:

Yes

38. Rack feed capacity:

60-40-20

39. Detergent and rinse pump system:

ProDose - accurate dosing with a peristaltic pump

40. Energy Saving system:

EnergySaving - Energy saving system due to lowering the boiler temperature

41. Rinse system:

ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure

42. Heating system:

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

43. Lift system:

ProGlide - Required lifting force equals 3 kg thanks to counterweights and gentle guidance, reduces operator fatigue

44. Hot water electric valve:

Yes

45. Closing door system:

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

46. Rack size [mm]:

500 x 500

47. Display type:

ProScreen - 4 digit display + 2 LED bars

48. Location of control panel:

On the top

49. USB port:

Yes, for Firmware actualisation

50. Drain pump:

Yes

Technical data sheet

Technical parameters



Hood type dishwasher double skin with drain pump 50x50 - 400 V

Model

SAP Code

00011289

51. Self-diagnostics:

Yes

52. Wash pump type:

two-way - DuoFlow

53. Detergent dispenser:

Yes

54. Rinse aid dispenser:

Yes

55. Water consumption of the washing cycle:

2,7

56. Washing cycle time [s]:

60-90-180

57. Rinse water temperature [°C]:

80

58. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

59. Additional information:

The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free

60. Program ProSpeed:

Yes

61. Program ProFessional:

Yes

62. Program ProTemp:

Yes

63. Program ProClean:

Yes

64. Program ProDrain:

Yes

65. Program ProEco:

Yes

66. Program ProLong:

Yes

67. Program ProGlass:

Yes