Product features



| Pot and pan washer double skin with drain pump 55x61 - 400 V | | | | |
|--|----------|--|--|--|
| Model | SAP Code | 00011970 | | |
| <image/> <image/> | | Display type: LCD multifunction d Number of programs: 11 Number of skin: 2 Door clear height [mm]: 850 Rack size [mm]: 560 x 630 Water consumption of the washin Detergent and rinse pump system dosing with a peristaltic pump Wash pump type: two-way - DuoF Self-cleaning cycle: Yes Drain filter: Evolution3 - double fi controlled partial discharge befor 0% loss of clean water to waste | g cycle: 3 1: ProDose - accurate Tow Itration with electronically | |
| SAP Code | 00011970 | Boiler capacity [l] | 12.00 | |
| Net Width [mm] | 782 | Boiler power [kW] | 6.000 | |
| Net Depth [mm] | 719 | Basin volume [l] | 37 | |
| Net Height [mm] | 1927 | Tank power [kW] | 3.000 | |
| Net Weight [kg] | 173.00 | Water consumption of the washing cycle | 3 | |
| Power electric [kW] | 10.500 | Door clear height [mm] | 850 | |

560 x 630


Loading

Rack size [mm]

400 V / 3N - 50 Hz

Technical drawing





Product benefits





Technical parameters



| Pot and pan washer double skin with drain pump 55x61 - 400 V | | | | |
|--|----------|--|--|--|
| Model | SAP Code | 00011970 | | |
| 1. SAP Code: | | 15. Number of programs: | | |
| 00011970 | | | | |
| 2. Net Width [mm]: 782 | | 16. Opening of device: Tilting down | | |
| 3. Net Depth [mm]: 719 | | 17. Door clear height [mm]: 850 | | |
| 4. Net Height [mm]: 1927 | | 18. Inlet pressure: 1-6bar | | |
| 5. Net Weight [kg]: 173.00 | | 19. Adjustable feet: Yes | | |
| 6. Gross Width [mm]: 870 | | 20. Number of skin: | | |
| 7. Gross depth [mm]: 890 | | 21. Self-cleaning cycle: Yes | | |
| 8. Gross Height [mm]: 2200 | | 22. Boiler capacity [l]: 12.00 | | |
| 9. Gross Weight [kg]: 183.00 | | 23. Boiler power [kW]: 6.000 | | |
| 10. Device type: Electric unit | | 24. Basin volume [l]: 37 | | |
| L 1. Control type: Digital | | 25. Tank power [kW]: 3.000 | | |
| L 2. Material: AISI 304 | | 26. Number of arms for both rinsing and washing: | | |
| 13. Power electric [kW]: 10.500 | | 27. Arm connection: Click-clack - easy removal with one hand | | |
| 14. Loading: 400 V / 3N - 50 Hz | | 28. Washing arm type: Rotating trident | | |

Technical parameters



| Model SAP Code | e 00011970 |
|--|---|
| 9. Washing arm material: Composite | 40. Energy Saving system: EnergySaving - Energy saving system due to lowering the boiler temperature |
| 0. Atmospheric boiler with rinse pump: Yes | 41. Rinse system: ProRinse - composite arms common for rinsing and washing with geometry for spraying water in thin jets directly against the dishes, the rinsing pump ensures constant pressure |
| 1. Rinsing arm type: Rotating trident | 42. Heating system: HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle |
| 2. Rinsing arm material: Composite | 43. Quick heating system: QuickReady - System for rapid heating of water in the tank |
| 3. Deep drawn tank: Yes | 44. Hot water electric valve: Yes |
| 4. Rack support: Pressed | 45. Closing door system: ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes |
| 5. Tank surface strainers: composite | 46. Rack size [mm]: 560 × 630 |
| 6. Drain filter: Evolution3 - double filtration with electronicall partial discharge before the rinsing phase ensu of clean water to waste | |
| 7. Thermostop: Yes | 48. USB port: Yes, for Firmware actualisation |
| 8. Boiler thermostat adjust: Yes | 49. Drain pump: Yes |

Technical parameters



| Pot and pan washer double skin with drain pump 55x61 - 400 V | | | | |
|--|------------------------------------|--|--|--|
| Model SAP Code | 00011970 | | | |
| | | | | |
| 51. Wash pump type: | 60. Program ProFessional 8: | | | |
| two-way - DuoFlow | Yes | | | |
| 52. Detergent dispenser: | 61. Program ProFessional 10: | | | |
| Yes | Yes | | | |
| 53. Rinse aid dispenser: | 62. Program ProClean: | | | |
| Yes | Yes | | | |
| 54. Water consumption of the washing cycle: | 63. Program ProDrain: Yes | | | |
| 55. Rinse water temperature [°C]: | 64. Program ProEco: | | | |
| 80-85 | Yes | | | |
| 56. Additional information: The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free | 65. Program ProLong: Yes | | | |
| 57. Program ProFessional 2: | 66. Program ProActive 5: | | | |
| Yes | Yes | | | |
| 58. Program ProFessional 4: | 67. Program ProActive 7: | | | |
| Yes | Yes | | | |
| 59. Program ProFessional 6: | - | | | |