# **Technical data sheet**



### **Product features**

| Conveyor toaster 2x holders with regulation |          |          |  |  |
|---|----------|----------|--|--|
| Model                                       | SAP Code | 00004519 |  |  |

- Material: Stainless steel
- Indicators: operation and warm-up
- Removable rear wall of the device: Yes
- Width of internal part [mm]: 305
- Depth of internal part [mm]: 500
- Heating location: Upper and lower

| SAP Code        | 00004519 | Net Weight [kg]     | 22.00              |
|-----------------|----------|---------------------|--------------------|
| Net Width [mm]  | 490      | Power electric [kW] | 3.200              |
| Net Depth [mm]  | 540      | Loading             | 230 V / 1N - 50 Hz |
| Net Height [mm] | 400      |                     |                    |

## **Technical data sheet**



**Product benefits** 

| Conveyor toaster 2x holders with regulation |          |          |  |  |
|---|----------|----------|--|--|
| Model                                       | SAP Code | 00004519 |  |  |

#### All-stainless design

only stainless steel intended for food contact is used

- absolutely rust-proof and non-magnetic design resists even weak acids easier compliance with hygiene standards (HACCP); easy maintenance and cleaning
- Run and warm-up light

optical possibility to check the status of the device

- the operator immediately knows the on/off, heating/ non-heating state of the appliance
- Separate control for individual sections the possibility of a heating system separately
  - greater variability of use
- Catch container for breadcrumbs
  breadcrumbs fall outside the furnace
   no crumbs falling off
- Continuous toaster
  automatic toast advance
   greater capacity
- Continuous feed adjustment
  possibility to change the speed of the sliding belt
  - ideally toasted according to the customer's wishes
- Silicon heaters
  immediate onset of heat
  intense radiant heat
  - the device can be switched off even during the operating day
  - toasted food vigorously and without overheating inside
  - faster food preparation

# **Technical data sheet**



### Technical parameters

| Conveyor toaster 2x holders wit   | h regulation |   |
|-----------------------------------|--------------|---|
| Model                             | SAP Code     | 00004519  |
|                                   |              |   |
| <b>1. SAP Code:</b> 00004519      |              | <b>12. Material:</b> Stainless steel              |
| 2. Net Width [mm]: 490            |              | 13. Power electric [kW]: 3.200                    |
| <b>3. Net Depth [mm]:</b> 540     |              | <b>14. Loading:</b> 230 V / 1N - 50 Hz            |
| 4. Net Height [mm]: 400           |              | <b>15. Heating element material:</b> Silicon tube |
| 5. Net Weight [kg]: 22.00         |              | <b>16. Protection of controls:</b> IPX4           |
| <b>6. Gross Width [mm]:</b> 515   |              | <b>17. Toasting time:</b> 60 – 240                |
| <b>7. Gross depth [mm]:</b> 750   |              | <b>18. Removable rear wall of the device:</b> Yes |
| 8. Gross Height [mm]:<br>440      |              | 19. Indicators: operation and warm-up             |
| 9. Gross Weight [kg]: 23.00       |              | <b>20. Width of internal part [mm]:</b> 305       |
| 10. Device type:<br>Electric unit |              | 21. Depth of internal part [mm]: 500              |
| 11. Construction type of device:  |              | 22. Heating location:                             |

Upper and lower

Table top