

# Technical data sheet

## Product features



### Undercounter dishwasher double skin 50x50 - 400 V

<b>Model</b>	<b>SAP Code</b>	00011288
--------------	-----------------	----------



- Display type: ProScreen - 4 digit display + 2 LED bars
- Number of programs: 7
- Number of skin: 2
- Door clear height [mm]: 465
- Rack size [mm]: 500 x 500
- Water consumption of the washing cycle: 1,8
- Washing cycle time [s]: 60-90-180
- Detergent and rinse pump system: ProDose - accurate dosing with a peristaltic pump
- Wash pump type: two-way - DuoFlow
- Self-cleaning cycle: Yes
- Drain filter: ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

<b>SAP Code</b>	00011288	<b>Boiler power [kW]</b>	6.000
<b>Net Width [mm]</b>	600	<b>Basin volume [l]</b>	15
<b>Net Depth [mm]</b>	600	<b>Tank power [kW]</b>	1.400
<b>Net Height [mm]</b>	1250	<b>Water consumption of the washing cycle</b>	1,8
<b>Net Weight [kg]</b>	63.00	<b>Washing cycle time [s]</b>	60-90-180
<b>Power electric [kW]</b>	7.900	<b>Door clear height [mm]</b>	465
<b>Loading</b>	400 V / 3N - 50 Hz	<b>Rack size [mm]</b>	500 x 500
<b>Boiler capacity [ l ]</b>	6.00	<b>Noise of device</b>	59,4


# Technical data sheet

Technical drawing



## Undercounter dishwasher double skin 50x50 - 400 V

<b>Model</b>	<b>SAP Code</b>	00011288
--------------	-----------------	----------



# Technical data sheet

## Product benefits



### Undercounter dishwasher double skin 50x50 - 400 V

Model

SAP Code

00011288

1

#### Stainless steel outer shell construction

round construction with stainless steel, rounded edges, Deep-drawn bathtub

- easy cleaning, high hygiene standard, long service life

2

#### Washing arms with a component, common for washing and rinsing

upper and lower composite swivel arms common for washing and rinsing with clickclack system for easy removal

- easy and safe handling during cleaning; higher user comfort

3

#### LED Display

proScreen 4 local display + 2 LED strips

- easy control of the dishwasher operation
- continuous information on the status of the wash cycle
- diagnostics in the event of a fault

4

#### Double pump

unique two-way DuoFlow pump

- distributes the water pressure evenly between the upper and lower arms; no noise; allows the use of a weaker pump

5

#### Molded basket supports

guide rails for the baskets molded from the body of the dishwasher

- high hygiene standard
- longer service life

6

#### Detergent dispensers

two detergent and rinse aid dispensers

- precise chemical dosing by ProDose - precise dosing system for detergent and rinse aid by peristaltic pump setting of values via control panel

7

#### Double filter system

the chamber filter and the waste filter together with the ArchiMedes system provide a discharge system with increased water purification efficiency

- higher washing efficiency; longer life of the washing bath

8

#### Energy saving

energy saving energy saving system due to lowering the temperature of the boiler

- cost saving

9

#### Protection of fragile dishes

softstart system for gradual start of washing programs to protect fragile dishes

- protects stemmed glasses and other fragile utensils

10

#### Double shell construction

stainless steel construction with insulated double jacket

- quiet operation
- energy saving

11

#### Fast heating

performance management allows the current running of the boiler and basins body

- quick first warm-up of the dishwasher
- smooth operation

# Technical data sheet

Technical parameters



## Undercounter dishwasher double skin 50x50 - 400 V

Model

SAP Code

00011288

**1. SAP Code:**

00011288

**2. Net Width [mm]:**

600

**3. Net Depth [mm]:**

600

**4. Net Height [mm]:**

1250

**5. Net Weight [kg]:**

63.00

**6. Gross Width [mm]:**

650

**7. Gross depth [mm]:**

650

**8. Gross Height [mm]:**

1300

**9. Gross Weight [kg]:**

69.00

**10. Device type:**

Electric unit

**11. Control type:**

Digital

**12. Material:**

Stainless steel

**13. Power electric [kW]:**

7.900

**14. Loading:**

400 V / 3N - 50 Hz

**15. Number of programs:**

7

**16. Opening of device:**

Tilting down

**17. Door clear height [mm]:**

465

**18. Inlet pressure:**

2-4bar

**19. Adjustable feet:**

Yes

**20. Number of skin:**

2

**21. Self-cleaning cycle:**

Yes

**22. Boiler capacity [ l ]:**

6.00

**23. Boiler power [kW]:**

6.000

**24. Basin volume [l]:**

15

**25. Tank power [kW]:**

1.400

**26. Number of arms for both rinsing and washing:**

2

**27. Arm connection:**

Click-clack - easy removal with one hand

**28. Washing arm type:**

Rotatable two-pronged

# Technical data sheet

## Technical parameters



### Undercounter dishwasher double skin 50x50 - 400 V

**Model**

**SAP Code**

00011288

**29. Washing arm material:**

Composite

**30. Rinsing arm type:**

Rotating two-pronged

**31. Rinsing arm material:**

Composite

**32. Deep drawn tank:**

Yes

**33. Rack support:**

Pressed

**34. Tank surface strainers:**

composite

**35. Drain filter:**

ArchiMedes - double filtration with overflow discharge ensures only 18% loss of clean water to waste

**36. Thermostop:**

Yes

**37. Boiler thermostat adjust:**

Yes

**38. Rack feed capacity:**

60-40-20

**39. Detergent and rinse pump system:**

ProDose - accurate dosing with a peristaltic pump

**40. Energy Saving system:**

EnergySaving - Energy saving system due to lowering the boiler temperature

**41. Heating system:**

HotWash - System of simultaneous operation of the heating element of the bath and the boiler, reducing the time for starting the next cycle

**42. Hot water electric valve:**

Yes

**43. Closing door system:**

ProSoft - Reduces noise, dampens the door stop, which could cause damage to dishes

**44. Rack size [mm]:**

500 x 500

**45. Display type:**

ProScreen - 4 digit display + 2 LED bars

**46. USB port:**

Yes, for Firmware actualisation

**47. Self-diagnostics:**

Yes

**48. Wash pump type:**

two-way - DuoFlow

**49. Detergent dispenser:**

Yes

**50. Rinse aid dispenser:**

Yes

**51. Water consumption of the washing cycle:**

1,8

**52. Washing cycle time [s]:**

60-90-180

# Technical data sheet

Technical parameters



## Undercounter dishwasher double skin 50x50 - 400 V

Model

SAP Code

00011288

### 53. Rinse water temperature [°C]:

80

### 54. Standard equipment for device:

1x glass basket, 1x plate basket, 1x cutlery basket

### 55. Additional information:

The product comes with 1x RM Clean+ 12 kg (00012271) and 1x RM Rinse+ 10 kg (00012273) for free

### 56. Program ProSpeed:

Yes

### 57. Program ProFessional:

Yes

### 58. Program ProTemp:

Yes

### 59. Program ProSelf:

Yes

### 60. Program ProEco:

Yes

### 61. Program ProLong:

Yes

### 62. Program ProGlass:

Yes

### 63. Noise of device:

59,4